

# Neuromuscular Stimulation

# The Sys\*Stim® 228



The new Sys\*Stim 228 neuromuscular stimulator features 4 discrete waveforms designed to facilitate clinical versatility. The Sys\*Stim 228 provides the flexibility to meet virtually any clinical need and has unprecedented ease of operation. Clinicians can choose from a broad range of waveforms, including Interferential, Pre-modulation, Medium Frequency (Russian Stim) and Biphasic with adjustable phase duration and frequency. Additional versatility is provided by a selection of treatment modes that include Surge, Reciprocation, Surge with Reciprocation and Vector Rotation. The Sys\*Stim 228 can be set up in the two-timer mode so two separate treatment protocols or two separate patients may be treated simultaneously.

**Weight:** 4.9 lbs. (2.2 kg)

**Dimensions:** 13 in. (L) x 8 in. (W) x 8 in. (T),  
(33 cm (L) x 20 cm (W) x 20 cm (T))

**Warranty:** 2 years

CE 0537

## Features

- 4 stimulation waveforms
- Easy to navigate user interface
- Bright color LED display
- Two independent timers

## SPECIFICATIONS

<b>Input:</b>	115 VAC ±10%, 50/60 Hz, 0.4 Amp Nom.
<b>Operating Temperature:</b>	+50°F to +131°F
<b>Humidity:</b>	Operating, 30% to 75% Relative Humidity at 104°F Nonoperating, up to 90% Relative Humidity at 149°F
<b>Storage Temperature:</b>	-40°F to 167°F
<b>Maximum treatment time:</b>	1-60 minutes
<b>Waveforms:</b>	Interferential, Premodulated, Medium Frequency (Russian), Biphasic
<b>Intensity:</b>	Interferential 0-65 mA RMS Premodulated 0-50 mA RMS Medium Frequency (Russian) 0-50 mA RMS Biphasic 0-99 mA peak



Mettler Electronics Corp.

For more information go to  
[www.MettlerElectronics.com](http://www.MettlerElectronics.com)  
or call 1 (800) 854-9305

Copyright © 2012 by Mettler Electronics Corp. - Anaheim, CA